

Gas detection tube polytest Dräger



Product Data

VOICE® - Hazardous substances database

Qualitative determination of oxidisable substances including measurement of concentration peaks, personal exposure in the inhalation area, detection of leaks in pipelines or gas installations, air analysis in sewers, shafts and confined spaces.

- Cross sensitivity based on the reaction principle ($\text{CO} + \text{I}_2\text{O}_5 \rightarrow \text{I}_2 + \text{CO}_2$), easily oxidised compounds indicated:
- 2000 ppm acetone ; 10 ppm acetylene ; 50 ppm ethylene ; 1 ppm arsine ; 10 ppm octane ; 50 ppm benzene
- 500 ppm propane ; 100 ppm butane ; 5 ppm carbon monoxide ; 10 ppm styrene
- 1 ppm carbon disulfide ; 20 ppm perchloroethylene ; 2 ppm hydrogen sulfide; 10 ppm toluene, Xylene
- Methane, ethane, hydrogen and carbon dioxide are not indicated.

Operating conditions:

Item No.	type no.	Standard measurement range [20 °C, 1.013 hPa]	Measuring time	Price
18.8509.39	Polytest	qualitativ	90 sec	CHF 61.00

* The prices are non-binding and are to be understood as selling prices in Swiss francs without value added tax (VAT), as well as all other fees, charges and taxes. The prices displayed in the eShop may differ from the PDF file due to regular updates.

** Please note that when ordering chemicals and detergents, transport and packaging costs for hazardous goods as well as legally prescribed fees are charged. These will be shown in detail on the order confirmation, which you will receive in addition to the confirmation of receipt.

*** Further information such as technical information and safety data sheets can be found online in our eShop.

**** The PDF file was created on www.huberlab.ch on 15.05.2024 at 20:42 oclock.