

Technical Datasheet

Date: 29.03.19

Page 1 of 1

EN ISO certified		
Article - No:	11-442-6000	Revision: 4
Remarks	max. volume: 100ml / working volume: 90 ml	single use only

Specification

Product	Screw cap container PP, 90ml, Ø50X75mm, cap pre-assembled, container transparent, cap green, grading 3 sided, every 10ml, sterile EO, autocl. up to 121°C, CE/IVD
Classification	CE/IVD
Colour	container transparent, cap green
Graduation	grading 3 sided, every 10ml
Nominal Capacity	90ml
Material Characteristics	container: polypropylene (PP) cap: high-density polyethylene (HDPE)
Temperature range	-40°C - 120°C
Autoclavability	autocl. up to 121°C
Product Characteristics	leak proof of not less than 95 KPa (0,95 bar, 14 psi) biologically inert physiologically harmless no heavy metals according to EC/94/62
Purity Grade	do not contain any pyrogens
Sterilisation Process	gas sterilisation by ethyleneoxid
Shelf - Life	36 months at controlled storage conditions
Packaging	pcs per bag: 200 pcs per carton: 200 pcs per pallet: 7.200
Storage	dry condition: 40%-60% rel. humidity bags / cases orig. closed storage temp. +2°C to max. +30°C pal. not stackable
Approved by nerbe plus quality department	