

Technical Datasheet

Date: 29.03.19

Page 1 of 1

| EN ISO certified | | |
|----------------------|--|------------------------|
| Article - No: | 11-452-6000 | Revision: 6 |
| Remarks | max. volume: 140ml / working volume: 125 ml | single use only |

Specification

| | |
|--|--|
| Product | Screw cap container PP, 125ml, Ø58X80mm, cap pre-assembled, container transparent, cap green, grading 3 sided, every 10ml, sterile EO, autocl. up to 121°C, CE/IVD |
| Classification | CE/IVD |
| Colour | container transparent, cap green |
| Graduation | grading 3 sided, every 10ml |
| Nominal Capacity | 125ml |
| Material Characteristics | container: polypropylene (PP) cap: high-density polyethylene (HDPE) |
| Temperature range | -40°C - 120°C |
| Autoclavability | autocl. up to 121°C |
| Product Characteristics | leak proof of not less than 95 KPa (0,95 bar, 14 psi) biologically inert physiologically harmless no heavy metals according to EC/94/62 |
| Purity Grade | do not contain any pyrogens |
| Sterilisation Process | gas sterilisation by ethyleneoxid |
| Shelf - Life | 36 months at controlled storage conditions |
| Packaging | pcs per bag: 150 pcs per carton: 150 pcs per pallet: 5.400 |
| Storage | dry condition: 40%-60% rel. humidity bags / cases orig. closed storage temp. +2°C to max. +30°C pal. not stackable |
| Approved by nerbe plus quality department | |