

# Technical Datasheet

Date: 15.05.17

Page 1 of 2

EN ISO certified		
<b>Article - No:</b>	<b>04-212-1000</b>	<b>Revision: 3</b>
<b>Remarks</b>	<b>piercable cap</b>	<b>single use only</b>

## Specification

<b>Product</b>	Microcentrifuge tube PP, 1,5ml, attached cap, transparent, graduated, with writing area, max. RCF 18.000g, autoclavable, CE/IVD
<b>Classification</b>	CE/IVD
<b>Dimensions</b>	tube: outer diameter 13,00 mm (+/- 0,2 mm) inner diameter: 10,80 mm (+/- 0,2 mm) height: 39,00 mm (+/- 0,2 mm) cap: length 20,00 mm (+/- 0,2 mm) width: 13,20 mm (+/- 0,2 mm) total height (tube and cap): 39,90 mm (+/- 0,2 mm)
<b>Colour</b>	transparent
<b>Graduation</b>	grad., writing area
<b>Nominal Capacity</b>	1,5ml
<b>Material Characteristics</b>	polypropylene (PP)
<b>Temperature range</b>	-70°C - 121°C
<b>Autoclavability</b>	autocl. up to 121°C
<b>Centrifugation</b>	max. RCF 18.000g
<b>Product Characteristics</b>	biologically inert physiologically harmless no heavy metals according to EC/94/62
<b>Purity Grade</b>	manufactured in clean rooms of ISO Class 8 or higher (DIN EN ISO 14644-1)
<b>Packaging</b>	pcs per bag: 1.000 pcs per carton: 8.000 pcs per pallet: 160.000
<b>Storage</b>	dry condition: 40%-60% rel. humidity bags & cases orig. closed