

Technical Datasheet

Date: 15.05.17

Page 1 of 2

| EN ISO certified | | |
|----------------------|----------------------|------------------------|
| Article - No: | 04-212-1005 | Revision: 2 |
| Remarks | piercable cap | single use only |

Specification

| | |
|---------------------------------|---|
| Product | Microcentrifuge tube PP, 1,5ml, attached cap, blue graduated, with writing area, max. RCF 18.000g, autoclavable up to 121°C, CE/IVD |
| Classification | CE/IVD |
| Dimensions | tube: outer diameter 13,00 mm (+/- 0,2 mm) inner diameter: 10,80 mm (+/- 0,2 mm) height: 39,00 mm (+/- 0,2 mm) cap: length 20,00 mm (+/- 0,2 mm) width: 13,20 mm (+/- 0,2 mm) total height (tube and cap): 39,90 mm (+/- 0,2 mm) |
| Colour | blue |
| Graduation | grad., writing area |
| Nominal Capacity | 1,5ml |
| Material Characteristics | polypropylene (PP) |
| Temperature range | -70°C - 121°C |
| Autoclavability | autocl. up to 121°C |
| Centrifugation | max. RCF 18.000g |
| Product Characteristics | biologically inert physiologically harmless no heavy metals according to EC/94/62 |
| Purity Grade | manufactured in clean rooms of ISO Class 8 or higher (DIN EN ISO 14644-1) |
| Packaging | pcs per bag: 1.000 pcs per carton: 8.000 pcs per pallet: 176.000 |
| Storage | dry condition: 40%-60% rel. humidity bags & cases orig. closed |