

# Technical Datasheet

Date: 21.08.17

Page 1 of 2

EN ISO certified		
<b>Article - No:</b>	<b>04-232-1206</b>	<b>Revision: 4</b>
<b>Remarks</b>	<b>piercable cap</b>	<b>single use only</b>

## Specification

<b>Product</b>	np Safelock-Cap microcentrifuge tube PP, 2ml, attached cap, boil-proof, amber, grad., writing area, np pcr ready, max. RCF 30.000g, autocl. up to 121°C, CE/IVD
<b>Classification</b>	CE/IVD
<b>Dimensions</b>	outer diameter: 10,80 mm (+/- 0,2 mm) height (without cap): 40,90 mm (+/- 0,2 mm)
<b>Colour</b>	amber
<b>Graduation</b>	grad., writing area
<b>Nominal Capacity</b>	2ml
<b>Material Characteristics</b>	polypropylene (PP)
<b>Temperature range</b>	-70°C - 121°C
<b>Autoclavability</b>	autocl. up to 121°C
<b>Centrifugation</b>	max. RCF 30.000g
<b>Product Characteristics</b>	biologically inert physiologically harmless constantly usable at temperature of 80 °C up to 100 °C
<b>Purity Grade</b>	free of PCR inhibitors free of human DNA free of RNase and DNase free of pyrogens
<b>Shelf - Life</b>	not limited at controlled storage conditions
<b>Packaging</b>	pcs per bag: 1.000 pcs per carton: 8.000 pcs per pallet: 160.000
<b>Storage</b>	dry condition: 40%-60% rel. humidity bags & cases orig. closed storage temp. +2°C to max. +30°C pal. not stackable