

# Technical Datasheet

Date: 15.06.17

Page 1 of 1

EN ISO certified		
<b>Article - No:</b>	<b>09-352-0070</b>	<b>Revision: 3</b>
<b>Remarks</b>	<b>max. vol.: approx. 65 l / working vol.: approx. 25 l</b>	<b>single use only</b>

## Specification

<b>Product</b>	Autoclavable bag PP, 600x800 mm, thickness: 70µm, natural, autoclavable up to 134°C
<b>Dimensions</b>	width: 600,00 mm (+/- 8 mm)
	length: 800,00 mm (-10/+20 mm)
	thickness: 70 µm (+/- 10%)
<b>Colour</b>	natural
<b>Material Characteristics</b>	polypropylene (PP)
<b>Autoclavability</b>	autocl. up to 134°C
<b>Product Characteristics</b>	biologically inert
	physiologically harmless
	extremely resilient double bottom seam
	density approx. 0,90 gr.
<b>Packaging</b>	pcs per cs: 200
	pcs per carton: 200
	pcs per pallet: 6.000
<b>Storage</b>	dry condition: 40%-60% rel. humidity
	bags & cases orig. closed
	storage temp. +10°C to max. +30°C
	pal. not stackable

**Approved by nerbe plus quality department**